

1. **PROPRIETARY PRODUCT**
Fiberglass reinforced with a polyester backing makes this product durable and easy to maintain.
Recommended areas for use: Residential
2. **PRODUCT DETAILS**
 - **Construction:** Urethane Topcoat Sealed (Low Gloss)
 - **Series:**
 - **Overall thickness:** .061" [1.6 mm]
 - **Wear Layer Thickness:** .010" [.25 mm]
 - **Widths:** 12' (3.6m)
 - **Maximum Roll Size:** 179 SYD [149.7 m]
 - **Weight per Square Yard:** 2.22 lbs/SYD [1.21 k/m]
3. **PRODUCT PERFORMANCE AND TECHNICAL DATA**
 - 3.1. **Flooring Radiant Panel:** ASTM E648, <.45w/cm²
 - 3.2. **Smoke:** ASTM E662, <450
 - 3.3. **HUD/FHA Minimum Property Standards:** Meets Wearlayer Thickness
 - 3.4. **FloorScore® Certification;** SCS-EC10.3-2014v4.0; SCS-SCS-FS-02746
 - 3.5. **Asthma and Allergy Certified:** AAFC 1541/18/05/01/2066
4. **ADHESIVE**
Tarkett QBond-One Adhesive
Tarkett 959 Vinyl Tile and Plank Adhesive
Permanent - Porous: 1/16" x 1/16" x 1/16" V-notch
Non-porous: 1/32" x 1/16" x 1/32" U-notch
Porous/Non-porous: Medium Nap Roller

Follow Instructions on the Adhesive Label.
5. **INSTALLATION – Follow the detailed Installations, visit www.tarkettna.com**
 - Installation System: Floating or Full Spread.
 - Maintain the work area, flooring and adhesive between 55° F and 95° F (12.8°C - 35°C) for 48 hours before, during and after installation. Maintain relative humidity between 40% and 70%.
 - ASTM F1869-10lbs; ASTM F2170-98%
 - Installations subjected to heavy traffic, caster action or requiring net fit must be fully adhered using Tarkett QBond-One™ or 959 Vinyl Tile and Plank Adhesive.
 - Seal and protect seams from all traffic for a minimum of 3 hours.

6. **SEAM METHOD**
Floating - Double-cut dry, use Tarkett S875 Floating Seam Tape under seams on all approved substrates.
Full Spread (Permanent) - Double-cut dry. Use Tarkett S860 Seam Tape.
7. **SEAM SEALER:** Tarkett DT-65 (Low Gloss)
8. **WARRANTY – For complete details contact Tarkett Technical Services or go to www.tarkettna.com**
 - 15 YEAR LIMITED RESIDENTIAL WARRANTY
9. **CARE AND MAINTENANCE**
 - When fully adhering, do not replace frequently moved furniture or allow heavy traffic for at least 24 hours.
 - Never slide heavy furniture or appliances across the floor. Place sheets of plywood over floor when moving furniture and appliances into position.
 - Maintain post installation temp. between 55° F and 95° F (12.8°C - 35°C). Maintain relative humidity between 40% and 70%.
 - Use non staining mats or area rugs at doorways and entranceways to collect excess water, sand, grit and debris. Clean the mats and area rugs on a regular basis.
 - Use smooth, hard plastic or metal furniture rests or glides under frequently moved furniture to avoid scratches and indentations. Do not use felt pads.
 - Wash floor with Tarkett SureShine® Floor Cleaner or equal neutral floor cleaner.
10. **TECHNICAL SERVICES**
For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit www.tarkettna.com or contact Tarkett at (888)-639-8297.



Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
888-639-8275 Fax 440-498-0025
northamerican.technicalsupport@tarkett.com

www.tarkettna.com