













TECHNICAL DATA

MANUFACTURER	ABSOLUT KERAMIKA		
PRODUCT TITLE SIZE AND MODEL TRADEMARK / GRADE	MONO 100 x 100mm / 200 x 200 mm		
MANUFACTURER (PROVIDED BY THE APPLICANT)		Date of reception	28/11/2011

ITEMS TESTED			REQUIRED STANDARD	RESULTS
Thickness			UNE-EN ISO 10545/2	7.8 mm
Length, width, thickness, side straightness, orthogonality and flatness.				CONFORM
Water absorption capacity			UNE-EN ISO 10545/3	15.5 %
Flexion resistance			UNE-EN ISO 10545/4	23 N/mm ²
Lineal thermic dilatation			UNE-EN ISO 10545/8	< 7·10 ⁻⁶ /°C
Thermic impact resistance			UNE-EN ISO 10545/9	CONFORM
Expansion due to moisture			UNE-EN ISO 10545/10	< 0'6 %
Cracking resistance			UNE-EN ISO 10545/11	CONFORM
Frost resistance			UNE-EN ISO 10545/12	CONFORM
Chemical resistance	Mild and strong, bases and acids		UNE-EN ISO 10545/13	Type GLA GHA
	Cleaning products and additives for swimming pool water			Type GA
Stains resistance			UNE-EN ISO 10545/14	Type5
Surface scratch resistance			UNE 67101 (EN 101)	MOHS 3
Radiatives test			—	Suitable for construction