

SPECIFICATIONS

PRODUCT / PRODUIT	VICTORY PARK
FIBRE / FIBER	100% SD OLEFIN
CONSTRUCTION	BOUCLÉ / LOOP
GAUGE	1/10"
POIDS DE FIBRE / PILE WEIGHT	23 oz
POIDS TOTAL / TOTAL WEIGHT	51.6 oz
POINTS PER POUCE / STITCHES PER INCH	14.7
DENSITÉ / DENSITY	229100
Endos Primaire / Primary Backing	NON TISSÉ / NON WOVEN
RÉPÉTITION DU MOTIF / PATTERN REPEAT	23.6" X 19.7"

SPÉCIFICATIONS DE PERFORMANCE / TECHNICAL PERFORMANCES

	NORME / STANDARD	VICTORY PARK
VOC (Green Label Plus)	ASTM D5116-06	<0.5 mg/m ² /hr
Inflammabilité / Flammability	ASTM D-2859// FF 1-70//16CFR 1630	Pass 8/8
Réaction au feu / Reaction to Fire	EN ISO 9239- 1:2002	Dfl - s1
Contrôle de la statique / Static Propensity	ISO 6356	0.2 kV
Résistance de la couleur / Color Fastness	AATC / 16	5/5 on Grey Scale
Résistance thermique / Thermal Resistance	ISO 8302	.04m ² .kW
Isolation acoustique / Impact Sound Insulation	ISO 140-8	23dB
Stabilité dimensionnelle / Dimensional Stability	EN 986	< 0.20%
Test chaise à roulettes / Castor Chair Test	DIN 54324	R ≥ 2.4

Ces informations peuvent changer sans préavis (11/2016) / The above Information is subject to modification for the benefit of further improvement (11/2016)

GARANTIE / WARRANTY
10 ans sur les taches et l'usure
10 Year on Stain and Wear

CENTURA 
VICTORY PARK